

### Description

Model MS010625 is a multi-octave high power amplifier operating from 1 to 6 GHz range with 30 Watts typical output power. It provides 54 dB of small signal gain with flatness  $\pm 2.0$  dB. MS010625 uses advanced GaN microwave device technology and provides long term reliability and high ruggedness. Hermetically sealed package implements reliable operation in various harsh environments.



### Features:

- 30 W RF Output Power
- 50 Ohm Input / Output Impedance
- Digital 5 - bit gain control (1 dB - 31 dB)
- Built-in output power detector
- High switching speed (300 ns)
- Gain - temperature compensation
- High reliability and ruggedness

### Applications:

- Communications Systems
- Test Instrumentation
- Broadband RF Telemetry
- Point To Point Radio
- Fiber Optics

### Electrical Specifications @ T=25°C, VDC = +27 V, Z<sub>s</sub>=Z<sub>L</sub>=50 Ω

Parameters	Symbol	Min	Typ	Max	Units
Operating Frequency	BW	1		6	GHz
RF Saturated Output Power	P <sub>sat</sub>	30	35		W
RF Output power @ at P <sub>in</sub> =3dBm	P <sub>3dBm</sub>	27	32		W
Small Signal Gain	G <sub>ss</sub>	50	54	60	dB
Small Signal Gain Flatness	ΔG		±2.0	±2.5	dB
VSWR Input / Output	VSWR In/Out		1.2 / 1.4	2.0 / 2.5	
Operating Voltage	VDC	26	27	30	V
Operating Current @ P <sub>sat</sub>	I <sub>DD</sub>			7.5	A

### Mechanical Specifications



Parameters	Value	Unit	Limits
Dimensions	147.5 x 78.6 x 24.0 (5.81 x 3.09 x 0.94)	mm (inch)	Max
Weight	0.45 (0.99)	kg (lb)	Max
RF Connectors, Input / Output	SMA (f)		
Interface connectors	X1: HWT M80-5101022		
	X2 : HWT HW22Y0202N		
Cooling	External Heatsink		

### Environmental Specifications

Parameters	Symbol	Min	Max	Unit
Operating Temperature (ambient)	T <sub>a</sub>	-55	+60	°C
Operating Temperature (baseplate)	T <sub>c</sub>	-55	+75	°C
Storage temperature	T <sub>stg</sub>	-65	+85	°C
Relative Humidity	RH		98	%

### Performance Plots

Test Conditions :  $T=25^{\circ}\text{C}$ ,  $Z_s=Z_L=50\Omega$



### DC Interface Connectors

Connector	Pin#	Description	Specification
X1 HWT M80-5101022	1	16	Bit 16 dB control
	2	8	Bit 8 dB control
	3	4	Bit 4 dB control
	4	2	Bit 2 dB control
	5	1	Bit 1 dB control
	6	DOUT	Power Detector Output
	7,10	G	Ground
	8	T	Analog Voltage Relative Temperature@10mV/°C
	9	Mod	RF Enable (0V or GND=RF Off, +5V or NC=RF On)
X2 HWT 22Y0202N	A	+27	DC Power (+26... +30VDC)
	B	G(-27)	Ground
	1,2	N/C	No Connection

### Mechanical Outline (All dimensions in millimeters)

